



# 6006

## High Build Block Filler Concrete Blocks Acrylic latex

### Technical Data Sheet

INTERIOR/EXTERIOR

#### Description

Proline 6006 is an acrylic latex high build block filler for new or bare concrete blocks for interior and exterior use. This block filler seals and levels the texture of the concrete blocks. It was developed to answer the needs of professional painters. The Proline 6006 can be used for commercial, industrial and residential projects.

#### Use

This block filler is applicable on interior and exterior surfaces. Proline 6006 must be applied to surfaces that have been well prepared. It is used to level the texture of concrete block walls.

#### Advantages

- The rheology of Proline 6006 is specially adapted to fill the cavities of highly irregular surfaces
- It contains specially formulated ingredients which allow for an application of more than 21 mils wet.
- Proline 6006 can be used as a topcoat when applied to an interior surface:

#### Limitations

- Avoid application under 10°C
- Do not apply under direct sunlight
- Do not use on flooring
- Wait 30 days before proceeding with the first cleaning
- Do not mix with other paints
- Do not apply on alkyd-based paints
- When used outdoors, it must be covered with an appropriate exterior topcoat

#### Technical Data

|                          |      |   |     |
|--------------------------|------|---|-----|
| Resin                    |      | Acrylic Latex                                     |     |
| Color                    |      | White   |     |
| Cleaning                 |      | Water   |     |
| Flash point              |      | N/A   |     |
| Inflammability           |      | N/A   |     |
| Solids by weight         |      | 71+/-2  | %   |
| Solids by volume         |      | 54+/-2  | %   |
| VOC                      |      | <50   | g/l |
| Gloss                    | 60°  | N/A   | %   |
| Sheen                    | 85°  | N/A   | %   |
| Standards/Certifications | LEED | Eligible for LEED® v4<br>CDPH Emissions Certified |     |
|                          | MPI  | Certified Categories #4                           |     |
|                          | ONGC | Type 1.188-2004.                                  |     |

#### Application Data

|  |  |                                     |        |
|--|--|-------------------------------------|--------|
| At 25° Celsius                                   |  |                                     |        |
| Relative humidity at 50%                         |  |                                     |        |
| May differ depending on the colour               |  |                                     |        |
| Spreading Rate                                   |  | 7-30 m <sup>2</sup><br>(75-325sqft) | gallon |
| <small>May vary depending on the surface</small> |  |                                     |        |
| Film Thickness                                   | Wet  | 5-21                                | mils   |
|  | Dry  | 2,7-11                              | mils   |
| Drying Time                                      | Tack free  | 30                                  | min    |
|  | Recoat   | 2-6                                 | hours  |
|  | Cleaning   | 30                                  | days   |
|  | Cure   | 30                                  | days   |
| Application                                      | Brush  | √                                   |        |
|  | Roller   | 20                                  | mm     |
|  | Spray*   | √                                   |        |
| <small>*More details APPLICATION section</small> |  |                                     |        |
| Exterior   | Plan for dry weather 48 hours after application if not topcoated |                                     |        |
| Storage  | Temperature  | 10-30                               | °C     |
| Tinted Bases                                     | Formats  |                                     |        |
|  | 946ml  | 3,78L                               | 18,9L  |
| 6006-0 White                                     |  |                                     | √      |



# 6006

High Build  
Block Filler  
Concrete Blocks  
Acrylic latex

## Technical Data Sheet

INTERIOR/EXTERIOR

### Surface preparation

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) in order to eliminate any contaminant that may affect the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.

Presence of mold: Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.

Concrete/Masonry: Wait until the concrete and/or masonry has cured at least 30 days before painting it

### Application

This product is ready to be used and does not require dilution. Mix well before use. Apply one coat or two if necessary. Allow a minimum drying time of 2 hours between each coat. In order to properly cover the surface, it is recommended to use a 20mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with lukewarm soapy water following their use.

For spray application:

Equipment: TITAN impact 840; 1gpm or larger

Pressure: Pump at 3000 lbs/in<sup>2</sup> ; gun 2200 lb/in<sup>2</sup>\*

Hose: 1st section: 1/4" x 50'

2nd section: 3/8" x 50'

Filter: Pump manifold, mesh 100 or 60

Spray Gun: RX-Pro

Nozzle: 0.25\*

\*This data may vary depending on the brand of the equipment manufacturer.

### Maintenance

It can be used as a topcoat if interior application. This paint requires 30 days drying time before proceeding with a first cleaning. Only use mild, non-abrasive cleaners and a soft cloth. Clean the surface with a light, circular motion.

### Warranty

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

### Caution

- Keep away from children's reach
- Keep lid closed when not in use
- Avoid freezing

**Contact your municipality to dispose of the container in an environmentally-friendly manner.**