

Technical Data Sheet

DESCRIPTION

Proline 207-0 flat finish is a concrete sealer of superior quality for indoor use. It is easy to apply and dries quickly. Proline 207-0 is formulated to meet the needs of professional painters.

USE

This sealer is applicable on interior surfaces. Proline 207-0 must be applied to surfaces that have been well prepared. It is formulated for concrete surfaces.

ADVANTAGES

- It seals concrete and masonry surfaces
- May give a darker look once it is dry.
- It contains Zero VOC.
- It dries in less than 4 hours and does not have a strong odour.
- It is possible to sand after 4 hours drying time

LIMITATIONS

- Avoid application under 10°C
- Not for exterior use
- Do not use on flooring

TECHNICAL DATA

Resin	Acrylic Latex		
Color	Clear		
Cleaning	Water		
Flash point	N/A		
Inflammability	N/A		
Solids by weight	25,5+/-2	%	
Solids by volume	21,7+/-2	%	
VOC	Zero VOC	g/l	
Gloss	60°	1	%
Sheen	85°	1	%
Standards / Certifications	LEED	Eligible for LEED® v4 CDPH Emissions Certified	

APPLICATION DATA

At 25° Celsius			
Relative humidity at 50%			
May differ depending on the colour			
Spreading Rate		37-46 m ²	gallon
<small>May vary depending on the surface</small>		(400-500sqft)	
Film Thickness	Wet	3,2-4,0	mils
	Dry	1,28-1,60	mils
Drying Time	Tack free	2-4	min
	Recoat	4	hours
	Cleaning	30	days
	Cure	30	days
Application	Brush	√	
	Roller	15	mm
	Spray* Nozzle: 0.011 – 0.015*	2000-2500	lb/100ft ²
<small>Max dilution 10%</small>			
<small>* These data may vary depending on the equipment manufacturer</small>			
Storage	Temperature	10-30	°C
Tinted Bases	Formats		
	946ml	3,78L	18,9L
207-0 Clear		√	√

Technical Data Sheet

SURFACE PREPARATION

The surface must be dry and clean, without dust, oil, grease, rust and soap. On painted surfaces, it is recommended to clean with a degreaser (T.S.P.) in order to eliminate any contaminant that may affect the adhesion or the curing of the product. Thoroughly rinse the entire surface. The surfaces must be well sanded and dusted.

Presence of mold: Clean the affected area with a mixture of 1 part bleach to 3 parts water. Thoroughly rinse the entire surface.

Concrete / Masonry: Wait until the concrete and/or masonry has cured at least 30 days before painting it.

APPLICATION

This product is ready to be used and does not require dilution. Mix well before use. Apply one coat or two if necessary. Allow a minimum drying time of 4 hours between each coat for pale colours and 8 hours for dark colours. In order to properly cover the surface, it is recommended to use a 15mm lint free roller and a quality nylon-polyester brush. Clean the brushes and rollers with lukewarm soapy water following their use.

For spray application: May be diluted with a maximum of 10% water.

Pressure: 2000 to 2500 lb/in²*

Nozzle: 0.011 – 0.015*

*This data may vary depending on the brand of the equipment manufacturer.

MAINTENANCE

This paint requires 30 days drying time before proceeding with a first cleaning. Only use mild, non-abrasive cleaners and a soft cloth. Clean the surface with a light, circular motion.

WARRANTY

This product will give full satisfaction if applied according to the manufacturer's instructions. Manufacturer's liability is limited to the replacement of the product and does not include manpower if found defective upon inspection.

CAUTION

- Keep away from children's reach
- Keep lid closed when not in use
- Avoid freezing

CONTACT YOUR MUNICIPALITY TO DISPOSE OF THE CONTAINER IN AN ENVIRONMENTALLY-FRIENDLY MANNER.